



MICRO MILLING

PREMIUM 3600

A high-quality polymer modified dry-set mortar blend of Portland cement, graded sand and special additives including redispersible polymers which are designed to improve adhesion and flexural strength, provide greater bond strength, and enhanced resistance to shock and impact.

Features:

- Suitable for installing porcelain tiles, ceramic tiles, clay tiles, cement tiles, glass tiles, quarry tiles, brick pavers, marble, natural stone, tile over tile* and tile over terrazzo*.
- For Commercial or Residential use.
- For Interior and exterior.
- For floors and walls.
- Superior flexibility and bond strength. Best for installing tile (including porcelain) over difficult substrates.
- Excellent adhesion to Exterior Grade Plywood (EGP) – interior applications only**
- Specially formulated for warm weather conditions.
- Resistant to shock and impact.
- Exceeds ANSI A118.4 standard for modified dry-set Portland cement tile mortar.
- Polymer Modified.
- Mix with water only.



Available in 22.7 kg./ 50 lbs size

Coverage:

Using a ¼" x ¼" (6x6mm) notched trowel on an evenly prepared surface, one bag will cover 30-50 sq. ft. (2.78- 4.65 m²).

* Proper physical preparation of terrazzo and tiled surfaces before tiling is required.

** Proper preparation of plywood surfaces using TEC Multipurpose Primer is needed. Please download our PDS at our website for additional details on surface preparation.