



PREMIUM LFT

Micro Milling Premium LFT thin set or medium-bed mortar is a polymer modified blend of Portland cement, graded sand and special additives for the installation of large format tiles.

Features:

- Ideal for installing 15" x 15" (38x 38 cm) and larger tiles.
- Suitable for porcelain tiles, ceramic tiles, marble and natural stone, tile over tile* and tile over terrazzo* applications.
- For Commercial or Residential uses.
- For Interior and exterior.
- For floors and walls.
- Ideal for installing tile (including porcelain) over difficult substrates.
- Excellent adhesion to Exterior Grade Plywood (EGP) - interior applications only**
- Can be used as a medium bed mortar up to 3/4" (19mm) thick.
- Special non slump formula helps eliminate lippage.
- Exceeds ANSI A118.4 standard for modified dry-set Portland cement tile mortar.
- Polymer Modified.
- Mix with water only.



Available in 22.7 kg./ 50 lbs size

Coverage:

Using a 1/2" x 1/2" (12 x12mm) notched trowel on an evenly prepared surface, one bag will cover 35-45 sq. ft. (3.26 -4.19 m²)

* Proper physical preparation of terrazzo and tiled surfaces before tiling is required.

** Proper preparation of plywood surfaces using TEC Multipurpose Primer is needed. Please download our PDS at our website for additional details on surface preparation.