



MICRO LEVEL 5000

Micro Milling's Micro Level 5000 is a specially formulated, dry blend of cement, fine graded aggregates, polymers and other additives that when mixed with water provides a flowable easily manageable, fast hardening concrete underlayment that is designed for use over various substrates to achieve a flat and level floor base.

Features:

- Self-levelling formulation - requires less effort and manpower to achieve a smooth level base ideal for modern building requirements.
- Fast drying and Rapid Strengthening – Accepts foot traffic in 24 hours.
- Low shrinkage.
- High Compressive Strength: ≥ 5000 psi.
- Pourable and Pumpable.
- Accepts Tile and Stone after 24 hours.
- For use between $\frac{1}{8}$ " - $\frac{3}{4}$ " (3-19mm) thick.
- Easy to use- Just add water.
- Additional height/thickness can be built up as required by repeating the process.



Available in 22.7 kg./ 50 lbs size

TECHNICAL FEATURES		
Coverage Guide		
Thickness	Approx Coverage	Water
$\frac{1}{8}$ " (3 mm)	44-48 ft ² (4.09 -4.46 m ²)	4.8 -5.3 US Qts. / 4.6 -5.0 Litres
$\frac{1}{4}$ " (6 mm)	22-24 ft ² (2.04 -2.23 m ²)	
$\frac{3}{8}$ " (9 mm)	5-16 ft ² (1.39 -1.49 m ²)	
$\frac{1}{2}$ " (12 mm)	11-12 ft ² (1.02 -1.12 m ²)	
$\frac{5}{8}$ " (16 mm)	8 $\frac{1}{2}$ -9 $\frac{1}{2}$ ft ² (0.79 -0.88 m ²)	
$\frac{3}{4}$ " (19 mm)	7 $\frac{1}{2}$ -8 ft ² (0.70 -0.74 m ²)	